



# JX STAMPING FASTENERS SERIES

## Q673C Spring Band Hose Clamps - Type B



Standard: Q673C,  
DIN 3021-1 (A)-1999  
QC/T 621.1-2013  
QC/T 621.2-2013  
QC/T 621.3-2013

Part Number Designation  
JX-Q673C-16-B-ST  
Type and Material: Carbon Steel  
Diameter Code: 16  
Type Code: B  
Material Code: ST

Part Number Designation  
JX-Q673C-16-B-SS  
Type and Material: Stainless Steel  
Diameter Code: 16  
Type Code: B  
Material Code: SS




Material: Carbon Steel,  
Spring steel, Stainless Steel

Unit:mm

Nominal diameter d	P/N		Delivery diameter d <sub>a</sub>	Full diameter d <sub>c</sub>	S	C	a max	b max	e ±0.7	g ±0.7	h max	t max
	Steel	Stainless steel										
13	JX-Q673C-13-B-ST	JX-Q673C-13-B-SS	12.0	14.2	0.8	12	12	4	7	5	60	0.09
14	JX-Q673C-14-B-ST	JX-Q673C-14-B-SS	13.3	15.8								
15	JX-Q673C-15-B-ST	JX-Q673C-15-B-SS	14.0	16.5								
16	JX-Q673C-16-B-ST	JX-Q673C-16-B-SS	14.9	17.5								
17	JX-Q673C-17-B-ST	JX-Q673C-17-B-SS	15.6	18.5								
18	JX-Q673C-18-B-ST	JX-Q673C-18-B-SS	16.0	19.0								
19	JX-Q673C-19-B-ST	JX-Q673C-19-B-SS	17.8	20.2								
20	JX-Q673C-20-B-ST	JX-Q673C-20-B-SS	18.4	21.6								
21	JX-Q673C-21-B-ST	JX-Q673C-21-B-SS	19.4	22.5								
22	JX-Q673C-22-B-ST	JX-Q673C-22-B-SS	20.5	24.2								
23	JX-Q673C-23-B-ST	JX-Q673C-23-B-SS	21.0	24.7	1.3	12	12	4	7	5	80	0.12
24	JX-Q673C-24-B-ST	JX-Q673C-24-B-SS	22.0	26.0								
25	JX-Q673C-25-B-ST	JX-Q673C-25-B-SS	23.5	26.3								
26	JX-Q673C-26-B-ST	JX-Q673C-26-B-SS	24.3	28.0								
27	JX-Q673C-27-B-ST	JX-Q673C-27-B-SS	25.2	29.0								
28	JX-Q673C-28-B-ST	JX-Q673C-28-B-SS	26.1	30.2								
29	JX-Q673C-29-B-ST	JX-Q673C-29-B-SS	27.0	31.5								
30	JX-Q673C-30-B-ST	JX-Q673C-30-B-SS	28.0	32.5								
32	JX-Q673C-32-B-ST	JX-Q673C-32-B-SS	29.5	34.5								
34	JX-Q673C-34-B-ST	JX-Q673C-34-B-SS	30.6	36.4								
35	JX-Q673C-35-B-ST	JX-Q673C-35-B-SS	31.5	38.0	2.1	12	12	4	7	5	92	0.15
36	JX-Q673C-36-B-ST	JX-Q673C-36-B-SS	32.5	39.0								
38	JX-Q673C-38-B-ST	JX-Q673C-38-B-SS	34.5	41.5								
40	JX-Q673C-40-B-ST	JX-Q673C-40-B-SS	35.5	42.5								
42	JX-Q673C-42-B-ST	JX-Q673C-42-B-SS	37.5	44.5								
43	JX-Q673C-43-B-ST	JX-Q673C-43-B-SS	37.9	45.5								
44	JX-Q673C-44-B-ST	JX-Q673C-44-B-SS	38.5	46.5								
46	JX-Q673C-46-B-ST	JX-Q673C-46-B-SS	40.5	48.5								
47	JX-Q673C-47-B-ST	JX-Q673C-47-B-SS	41.5	50.0								
49	JX-Q673C-49-B-ST	JX-Q673C-49-B-SS	42.5	52.0								
50	JX-Q673C-50-B-ST	JX-Q673C-50-B-SS	43.5	53.0	2.6	12	12	4	7	5	110	0.15
51	JX-Q673C-51-B-ST	JX-Q673C-51-B-SS	44.0	54.0								
53	JX-Q673C-53-B-ST	JX-Q673C-53-B-SS	46.0	55.8								
55	JX-Q673C-55-B-ST	JX-Q673C-55-B-SS	47.0	58.0								
60	JX-Q673C-60-B-ST	JX-Q673C-60-B-SS	51.5	63.0								
65	JX-Q673C-65-B-ST	JX-Q673C-65-B-SS	57.5	68.0								
70	JX-Q673C-70-B-ST	JX-Q673C-70-B-SS	61.5	73.0								
75	JX-Q673C-75-B-ST	JX-Q673C-75-B-SS	66.0	78.0								
80	JX-Q673C-80-B-ST	JX-Q673C-80-B-SS	70.0	83.0								
85	JX-Q673C-85-B-ST	JX-Q673C-85-B-SS	74.0	88.0								
90	JX-Q673C-90-B-ST	JX-Q673C-90-B-SS	79.0	93.0								

# JX STAMPING FASTENERS SERIES

## Mini screw hose clamp (MC)






Material: 65MN, Carbon steel, Stainless steel

Unit:mm/inch

Size	P/N			A				B		C		D
	65MN	Carbon steel	Stainless steel	min.		max.		mm	inch	mm	inch	
				mm	inch	mm	inch					
7	JX-MC-7-65MN	JX-MC-7-CS	JX-MC-7-SS	6	.24	8	.31	9	.35	0.6	.024	7
8	JX-MC-8-65MN	JX-MC-8-CS	JX-MC-8-SS	7	.28	9	.35					
9	JX-MC-9-65MN	JX-MC-9-CS	JX-MC-9-SS	8	.31	10	.39					
10	JX-MC-10-65MN	JX-MC-10-CS	JX-MC-10-SS	9	.35	11	.43					
11	JX-MC-11-65MN	JX-MC-11-CS	JX-MC-11-SS	10	.39	12	.47					
12	JX-MC-12-65MN	JX-MC-12-CS	JX-MC-12-SS	11	.43	13	.51					
13	JX-MC-13-65MN	JX-MC-13-CS	JX-MC-13-SS	12	.47	14	.55					
14	JX-MC-14-65MN	JX-MC-14-CS	JX-MC-14-SS	13	.51	15	.59					
15	JX-MC-15-65MN	JX-MC-15-CS	JX-MC-15-SS	14	.55	16	.63					
16	JX-MC-16-65MN	JX-MC-16-CS	JX-MC-16-SS	15	.59	17	.67					
17	JX-MC-17-65MN	JX-MC-17-CS	JX-MC-17-SS	16	.63	18	.71					
18	JX-MC-18-65MN	JX-MC-18-CS	JX-MC-18-SS	17	.67	19	.75					
19	JX-MC-19-65MN	JX-MC-19-CS	JX-MC-19-SS	18	.71	20	.79					
20	JX-MC-20-65MN	JX-MC-20-CS	JX-MC-20-SS	19	.75	21	.83					
21	JX-MC-21-65MN	JX-MC-21-CS	JX-MC-21-SS	20	.79	22	.87					
22	JX-MC-22-65MN	JX-MC-22-CS	JX-MC-22-SS	21	.83	23	.91					
23	JX-MC-23-65MN	JX-MC-23-CS	JX-MC-23-SS	22	.87	24	.94					
24	JX-MC-24-65MN	JX-MC-24-CS	JX-MC-24-SS	23	.91	25	.98					
25	JX-MC-25-65MN	JX-MC-25-CS	JX-MC-25-SS	24	.94	26	1.02					
26	JX-MC-26-65MN	JX-MC-26-CS	JX-MC-26-SS	25	.98	27	1.06					
27	JX-MC-27-65MN	JX-MC-27-CS	JX-MC-27-SS	26	1.02	28	1.1					
28	JX-MC-28-65MN	JX-MC-28-CS	JX-MC-28-SS	27	1.06	29	1.14					
29	JX-MC-29-65MN	JX-MC-29-CS	JX-MC-29-SS	28	1.1	30	1.18					
30	JX-MC-30-65MN	JX-MC-30-CS	JX-MC-30-SS	29	1.14	31	1.22					

## DIN3016-2-2000 Coupling - H1/H2 type



Material: 65MN, Carbon steel, Stainless steel

Unit:mm

Size	P/N			d1	b			b1		h2	L	d2	S1
	65MN	Carbon steel	Stainless steel		max.	min.	nom.	max.	min.				
9	JX-DIN3016-9-65MN	JX-DIN3016-9-CS	JX-DIN3016-9-SS	7-68	9.3	8.7	13	13.8	12.2	12	31	M4	—
12	JX-DIN3016-12-65MN	JX-DIN3016-12-CS	JX-DIN3016-12-SS	10-78	12.3	11.7	15	15.8	14.2	14.5	35	M5	8
15	JX-DIN3016-15-65MN	JX-DIN3016-15-CS	JX-DIN3016-15-SS	17-97	15.3	14.7	19	20	18	15	40	M6	10
20	JX-DIN3016-20-65MN	JX-DIN3016-20-CS	JX-DIN3016-20-SS	21-126	20.3	19.7	25	26	24	20	46	M8	13
25	JX-DIN3016-25-65MN	JX-DIN3016-25-CS	JX-DIN3016-25-SS	34-144	25.3	24.7	31	32.3	29.7	25	55	M10	16
30	JX-DIN3016-30-65MN	JX-DIN3016-30-CS	JX-DIN3016-30-SS	69-500	30.3	29.7	36	37.3	34.7	33	75	M12	18